

```

<HTML>
<HEAD>
<TITLE>7月号 tips2</TITLE>

<LINK href="spring.css"; title="css1" TYPE="text/css" rel="stylesheet">
<LINK href="summer.css"; title="css2" TYPE="text/css" rel="stylesheet">
<LINK href="autumn.css"; title="css3" TYPE="text/css" rel="stylesheet">

<SCRIPT Language="JavaScript">
<!--
  var st = document.styleSheets;
  accTime = new Date();
  accHour = accTime.getHours();

  if(accHour >= 7 && accHour < 15) aName = "css1";
  else if(accHour >= 15 && accHour < 23) aName = "css2";
  else aName = "css3";

  if(st){ for (var i = 0; i < st.length; i++){
    if(aName && (st[i].title == aName || st[i].title == ""))
      st[i].disabled = false;
    else st[i].disabled = true;
  }
}
//-->
</SCRIPT>

</HEAD>
<BODY>
<H1>HTML TIPS & TRICKS</H1>
</BODY>
</HTML>

```

title 属性にアクセスしているので、NN6 でもOK

```

<SCRIPT TYPE="text/javascript">
now = new Date(); h = now.getHours();
if(6 <= h && h < 12) a = 0;
else if(12 <= h && h < 18) a = 1;
else a = 2;
for (i = 0; i < 3; i++) {
  document.styleSheets[i].disabled = (i == a) ? false : true;
}
</SCRIPT>

```

#### spring.css

```
BODY { background-image: url(back-01.gif); color: #ff0000}
```

```
H1 { border: 3px solid #ff0000; margin-left: 20px;padding: 5px 20px;
background-color: #fed0e0; font: bold 40px Verdana Bold;}
```



#### summer.css

```
BODY { background-image: url(back-02.gif); color: #1e90ff}
```

```
H1 { border: 3px solid #1e90ff; margin-left: 20px;padding: 5px 20px;
background-color: #87ceeb; font: bold 40px Verdana Bold;}
```



#### autumn.css

```
BODY { background-image: url(back-03.gif); color: #a52a2a}
```

```
H1 { border: 3px solid #a52a2a; margin-left: 20px;padding: 5px 20px;
background-color: #daa520; font: bold 40px Verdana Bold;}
```

